



LUGA Gateway

FEATURES & BENEFITS

- Messaging and/or voice communication
- Connects to TDM's NIS control system
- 2 and 4 channels versions available
- Supports VoIP
- Connects to PSTN via the NIS
- GSM Help Point monitoring
- Integration with a higher system via the NIS
- Increased network availability with multiple providers
- Remote Help Point configuration
- Fallback call system

PRODUCT DESCRIPTION

The LUGA Gateway provides the GSM/LTE/UMTS wireless connection between TDM's GSM Help Points and the NIS control system, converting the incoming and outgoing mobile calls to VoIP. The gateway also handles the messaging between the Help Points and the NIS, allowing for configuration and monitoring to be carried out via SMS.

Help Point call status and statistics can be forwarded by the NIS system to a higher system via a CTI, OPC or SNMP interface.

| SPECIFICATIONS | | GENERAL | |
|----------------|----------------------|----------|--------------------------------------|
| Dimensions | 482mm x 472mm x 88mm | Mounting | Rack Mounted |
| Weight | Approx. 8kg | MTBF | 80,000 hrs (single chassis), at 35°C |
| Rating | IP20 | MART | 0.5 Hrs (single chassis) |

Trans Data Management Ltd

For more information contact us: +44 (0) 1293 516 691 - info@trans-data.co.uk

Although the information in this publication is represented in good faith and believed to be correct, TRANS DATA MANAGEMENT LTD makes no representations or warranties as to the completeness or accuracy of the information. In no event will TDM be responsible for damages of any nature whatsoever resulting from the use of or reliance upon the information contained in this document. Such information is subject to change without notice. The graphics and contents of this document are the copyrighted work of TDM and contain proprietary trademarks and trade names of TDM.